



PETROL BOYS

PBCLT52067

0W-40 MG/FHX

High performance fuel saving fully synthetic oil, suitable for all gasoline and diesel engines of the latest generation, with and without turbocharger. General type with fuel saving benefits, formulated with high quality synthetic base oils, PolyAlphaOlefin (PAO) and combined with a special selected additive package.

TYPICALS

Density at 15°C, kg/l	:	0,845
Viscosity -35°C, cP	:	6200
Viscosity 40°C, mm ² /s	:	80,9
Viscosity 100°C, mm ² /s	:	14,6
Viscosity Index	:	189
Flash Point COC, °C	:	>201
Pour Point, °C	:	-45
Total Base Number, mgKOH/g	:	10,0

APPLICATIONS

0W-40 MG/FHX is formulated with high quality synthetic base oils, PolyAlphaOlefin (PAO), in combination with a special selected additive package to ensure the following properties:

- Excellent thermal and oxidation stability
- Fuel saving properties
- Excellent protection against wear, foam en corrosion
- High viscosity index in a wide range of ambient conditions
- Low temperature properties, to ensure a smooth cold start

PERFORMANCE LEVEL

APPROVAL: MB 229.5
 API SN/CF
 ACEA A3/B4
 BMW LONGLIFE-01
 FORD WSS-M2C937-A
 MB 229.3
 PORSCHE A40
 RENAULT RN 0700/0710
 VW 502.00/505.00

This information was composed to the best of our current knowledge. It provides no guarantees. The data in this sheet is a result of extensive testing by Petrol Boys Co. or its suppliers. However always thoroughly check whether the product is fit to serve the purpose you mean it to work for.