



**PBCLT58067** 

## **5W-30** MS/FHX

Universal high performance, fuel saving, MID SAPS, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. A high performance fuel saving MID SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger car and light vans with or without turbocharger.

## **TYPICALS**

Density at 15°C, kg/l 0,850 Viscosity 40°C, mm<sup>2</sup>/s 65 Viscosity 100°C, mm<sup>2</sup>/s 11,7 Viscosity Index 175 Flash Point COC >218°C **Pour Point** -39°C Total Base Number, mgKOH/g : 7,6 Sulphpate Ash, % 0,8

## **APPLICATIONS**

5W-30 MS/FHX is based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Reducing fuel consumption
- Excellent mid SAPS content
- Excellent corrosion protection
- Very suitable for modern (diesel) catalysts
- Excellent protection at low temperatures taking care of effortless cold starts
- Excellent antiwear and antifoam properties
- · Good thermal and oxidation stability.

## PERFORMANCE LEVEL

APPROVAL FOR: MB 229.51

ACEA C3
API SN/CF
BMW LONGLIFE-04
GM Dexos 2
Renault RN 0700

This information was composed to the best of our current knowledge. It provides no guarantees. The data in this sheet is a result of extensive testing by Petrol Boys Co. or its suppliers. However always thoroughly check whether the product is fit to serve the purpose you mean it to work for.