



PETROL BOYS

PBCLW502016

10W-40 MG/FHX

Fully synthetic lubricant based on carefully selected very high quality base oils, providing outstanding wear and sludge protection, even under the most severe driving conditions. Due to its enhanced frictional properties, improved fuel economy is obtained.

TYPICALS

Density at 15°C, kg/l	:	0,852
Viscosity 40°C, mm ² /s	:	64,00
Viscosity 100°C, mm ² /s	:	10,60
Viscosity Index	:	156
Flash Point COC °C	:	234
Pour Point °C	:	-42
Total Base Number, mgKOH/g	:	8,1
Sulphated Ash, Mass %	:	0,88

APPLICATIONS

10W-30 MG/FHX is a motor oil that has been specially designed to meet the latest requirements for most american and asian passenger cars, SUV's and light vans. originally intended for fuel-injected gasoline engines, including turbo-charging and multi-valves, it can also be used in light duty diesel engines without particulate filters.:

- Excellent protection against wear, corrosion and foaming
- Strong resistance against oxidation
- Safe lubrication film at high temperature
- Excellent detergency, dispersion and durability properties
- Excellent fluidity at low temperature, ensuring effortless cold starts

PERFORMANCE LEVEL

ACEA A3/B3
A3/B4
API SL/CF