



# PETROL BOYS

PBCLT58097

## 10W-30 MG/SMX SN

This is a high performance fuel saving engine oil based on synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a ACEA A3/B4 specification is required and suitable for all engines which require an MB 229.3 and VW 502.00 performance specification.

## TYPICALS

|                            |   |       |
|----------------------------|---|-------|
| Density at 15°C, kg/l      | : | 0,869 |
| Viscosity -25°C, cP        | : | 7000  |
| Viscosity 40°C, mm²/s      | : | 79,00 |
| Viscosity 100°C, mm²/s     | : | 11,98 |
| Viscosity Index            | : | 165   |
| Flash Point COC, °C        | : | >201  |
| Pour Point, °C             | : | -36   |
| Total Base Number, mgKOH/g | : | 10    |
| Sulphated ash, %Wt         | : | 1,31  |

## APPLICATIONS

10W-30 MG/SMX SN is based on synthetic technology base oil in combination with a specially selected additive technology to ensure the following properties::

- Excellent thermal and oxidation stability
- Fuel saving properties
- Excellent protection against wear, foam and corrosion
- Low temperature properties, to ensure a smooth cold start
- Long oil drain interval possible

## PERFORMANCE LEVEL

API SN/CF  
ACEA A3/B4  
VW 502.00/505.00  
MB 229.3