



PETROL BOYS

PBCLW502014

5W-30 MS/SMX

Special synthetic based engine oil meeting the specifications of different OEMs. Its mid SAPS formulation combines excellent low viscosity properties with highly protective additives, enabling the engine to run more fuel efficient.

TYPICALS

Density at 15°C, kg/l	:	0,850
Viscosity 40°C, mm ² /s	:	67,50
Viscosity 100°C, mm ² /s	:	11,80
Viscosity Index	:	172
Flash Point COC	:	232°C
Pour Point	:	-39°C
Total Base Number, mgKOH/g	:	7,0
Sulphate Ash, %	:	0,79

APPLICATIONS

This engine oil meets the dexos 2 specifications, which means that it can be used to lubricate all new GM/OPEL/Vauxhall and Chevrolet diesel and gasoline passenger cars. Furthermore, it meets different demanding Volkswagen and Mercedes-Benz specifications. Based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- Reducing fuel consumption
- Supporting cold start
- Suitable for modern catalyts
- Excellent mid-SAPS properties
- Extended oil drain intervals
- Good detergency and dispersion
- Good protection against wear, corrosion and foaming

PERFORMANCE LEVEL

ACEA C3
 API SN/CF
 BMW LONGLIFE-04
 GM dexos 2
 MB 229.51/229.52
 VW 505.01/505.00